Geotech Grundfos Redi-Flo 2 Pump and Controller

Redi-Flo2® electrical submersible pump provides smooth, uninterrupted water flow during ground water sampling to depths down to 280 feet. Both high flow rates needed for purging and low flows recommended for sampling are achieved with the same pump. Designed for long-term reliability in dedicated monitoring wells, the Redi-Flo2® provides optimal sample quality. Whether doing traditional purging prior to sampling or low draw-down passive sampling when operated with the Redi-Flo VFD (Variable Frequency Drive) flow control is easy! Purging and sampling with the same pump is extremely efficient. The unique design and superior materials allow for easy operation, decontamination and maintenance as well as disassembly and reassembly.

Specifications

Operating Conditions

1°C (34°F) to 28°C (80°F)

Connections

1/2” Female NPT

Lead Wire

Lead Lengths are 300 ft.

Features

- 1.8” Diameter
- Flow ranges from 8 GPM to as little as 100ml/min
- Continuous flow
- Low velocities and agitation

Accessories

- Silicone Tubing
- Ground Water Filters
- Nitrile Glove
- Extra Battery Available
- Car Battery Adapter

9333 - 41 Avenue
Edmonton, AB
Ph. (780) 469.1356
Fax (780) 469.2587

4511 Manhattan Road SE
Calgary, AB
Ph. (403) 287.2805
Fax (403) 287.3597

#34, 147 Citation Drive
Vaughan, ON
Ph. (905) 760.0170
Fax (905) 760.0171

1.888.RICEENG
www.ricerentals.ca